

# Petra Universal Synthetic ATF Fluid

## PN 52003 (3gal) Specification Sheet



### Product Description:

Petra universal ATF is specially formulated for the latest generation of high efficiency automatic gear transmissions of all North American, European and Asian passenger and commercial vehicles. Helps provide exceptional oxidation, wear frictional stability, sludge and deposit prevention, and anti-shudder properties required in today's high performance transmissions. Also designed to deliver premium performance in older transmissions

### Suitable Uses\*\*:

- Asin Warner AW-1
- Allison C-4
- Allison TES 295
- Allison TES-389, TES-389B
- Audi G 052 162, G 052 990, G 055 025
- Audi G 055 005, G 055 162, G 052 540
- BMW 7045E, BMW 8072B, LA 2634, LT 71141
- BMW 82 22 0 142 516
- Chrysler MS-10838 P/N 05142893AA
- Chrysler MS-1872, MS-5931, P/N 04883077, MS 9602
- DSIH6p805 (Geely, Ssangyong, Mahindra 6sp)
- Ford M
- FordM2C195-A
- Ford Part #XL-12
- GM Auto Trak II
- GM P/N 12345866 (GM 9985835)
- GM P/N 89021184, P/N 1052884 (GM 9985010)
- GM- IID, IIIG, IIHH
- Honda ATD Z-1
- Honda DW-1
- Hyundai NWS-9638
- Hyundai/Kia PFS 3
- Hyundai/Kia SP-II, SP-III, JWS 3314, JWS 3317
- Hyundai/Kia SP-IV, SPH-IV, SP-IV RR
- IdemitsuK17 (JATCO)
- JASO 1-A
- JASO1-A-LV

- JWS 3309 (Asian Warner)
- JWS 3324
- Kia Red -1
- MAN 339 Type Z-1
- MAN 339F, 339 Type V-I
- Mazda ATF-M III, ATF-MV
- Mercedes GL-450 (ATF 3403)
- Mercedes-Benz 236.1, 236.2, 236.2, 236.6, 236.7, 236.9, 236.11, 236.81
- Mercedes-Benz 236.12, 236.14, 236.15
- Mercedes-Benz 236.3 (P/N 000 989 88 03)
- Mercedes-Benz 236.41
- Mercedes-Benz 238.91
- Mercedes-Benz; MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10 (NAG 1/Shell 3403) 236.11, 236.81
- Mitsubishi ATF-J3, ATF-PA
- Mitsubishi PS fluid, Diamond SP-III
- Mitsubishi SP-II, SP-III, DiaqueenATF J2
- Mitsubishi SP-IV
- Nissan 402, Nissan Matic-D,J,K
- Nissan MaticS, MaticW
- Nissan PSF-II
- North American models (DEXRON VI, MERCON LV)
- Other North America high viscosity ATF (MERCON V, ATF+4)
- PSA AL-4
- Renault DP-0
- Saab 93 165 147
- Saab P/N 45 30 09 800
- Subaru ATF, ATF-HP
- Subaru P/N K0209A0080



- Suzuki 3314, 3317
- Texaco N402 (JATCO), ETL-7045E (BMW 7045E), ETL-8072B (BMW 5 Sp)
- Toyota PSF Type EH P/N 008886-01
- Toyota T, T-II, T-III, T-IV
- Toyota WS (JWS 3324)
- VoithH55.6335
- Volvo 4 speed (P/N 1161621)
- Volvo 5/6 speed (P/N1161540/1161640)
- Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675)
- Volvo 97340, 97341
- VW G 052 162, G 052 990, G 055 025
- VW G 052 540, G 055 005, G 055 162
- ZF 6 speed (S671 090 255)
- ZF TE-ML 03D, 04D, 05L, 16L, 17C
- ZF TE-ML 09
- ZF TE-ML 11(3/4/5)
- ZF TE-ML 14A
- ZF TE-ML 21L

**\*Viscosity requirement not met\***

**\*\*Not recommended for CVT, DCT and Type F applications\*\***